

CTS CPVC Hot & Cold Water Distribution System
EverTUFF® CPVC CTS Fittings, Valves, Pipe & Cement

EverTUFF® CPVC CTS Fittings, Valves, Pipe & Cement



PRICING

P
LASCO

**Welding &
Fabrication Inc.**

4268 Dundas St.
Thorndale, On N0M 2P0
1.888.475.2726
www.plascowelding.com

CTS CPVC Hot & Cold Water Distribution System
EverTUFF® CPVC CTS Fittings, Valves, Pipe & Cement

PRODUCT INFORMATION

APPLICATION	PRODUCT CERTIFICATION
Spears® Copper Tube Size (CTS) fittings are manufactured from chlorinated polyvinyl chloride (CPVC) for Spears® CPVC CTS fittings and Special Reinforced (SR) Thread transition adapters are tested and use with SDR-11 piping systems of CTS outside diameter in hot and cold water distribution systems. certified by the National Sanitation Foundation (NSF®) to ASTM D 2846 for use in Hot and Cold Water Distribution Systems, and for safe use in potable water systems under NSF® Standard 14/61.	Spears® CPVC CTS fittings and Special Reinforced (SR) Thread transition adapters are tested and use with SDR-11 piping systems of CTS outside diameter in hot and cold water distribution systems. certified by the National Sanitation Foundation (NSF®) to ASTM D 2846 for use in Hot and Cold Water Distribution Systems, and for safe use in potable water systems under NSF® Standard 14/61.
CONFORMANCE STANDARDS	TESTING
Spears® CPVC CTS fittings conform to ASTM D 2846 Specification for Chlorinated Poly (Vinyl Chloride) (CPVC) Plastic Hot and Cold Water Distribution Systems.	Once the system has been installed and allowed to cure properly, the system shall be tested in accordance with applicable code requirements. When testing with water (hydrostatic testing), the system must be slowly filled with water and the air bled from the highest and furthest points in the system before test pressure is applied. Failure to do so can cause damage to the piping system and could be harmful to the job site personnel should a failure occur. If a leak is found, the affected product must be cut out and discarded. A new section can be installed using couplings or other approved means.
WORKING PRESSURE	
Spears® CPVC CTS fittings have a continuous working pressure rating of 100 psi at 180°F (82°C) [400 psi at 73°F (23°C)].	

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	Price Each
-------------	------	--------	----------	-----------	------------

TEE

Socket x Socket x Socket



4101-005	1/2	25	300	035	1.56
4101-007	3/4	25	200	035	2.92
4101-010	1	10	120	035	15.31
4101-012	1-1/4	10	80	035	23.48
4101-015	1-1/2	5	60	035	30.59
4101-020	2	5	0	035	49.45

DROP EAR TEE (Fitting with Bracket)

Socket x Socket x Socket



DE4101-005	1/2	25	150	035	3.32
------------	-----	----	-----	-----	------

DROP EAR BRACKET ONLY

For 4101-005 and 4106-005



DES-005	1/2	800	0	035	6.17
---------	-----	-----	---	-----	------

REDUCING TEE

Socket x Socket x Socket



4101-074	1/2X1/2X3/4	25	300	035	5.42
4101-094	3/4X1/2X1/2	25	300	035	2.91
4101-095	3/4X1/2X3/4	25	300	035	2.91
4101-101	3/4X3/4X1/2	25	300	035	3.01
4101-102*	3/4X3/4X1	10	60	035	33.77
4101-120*	1X1/2X1/2	10	120	035	36.39
4101-122*	1X1/2X1	10	120	035	27.52
4101-124*	1X3/4X1/2	10	120	035	34.28
4101-125	1X3/4X3/4	10	120	035	18.56
4101-126*	1X3/4X1	10	120	035	25.73
4101-130	1X1X1/2	10	120	035	17.39
4101-131	1X1X3/4	10	120	035	16.59
4101-138*	1-1/4X1/2X1/2	10	80	035	45.34
4101-139*	1-1/4X1/2X3/4	10	80	035	45.34
4101-142*	1-1/4X1/2X1-1/4	10	80	035	40.16
4101-146*	1-1/4X3/4X1/2	10	80	035	45.34
4101-147*	1-1/4X3/4X3/4	10	80	035	45.34
4101-148*	1-1/4X3/4X1	10	80	035	45.34
4101-149*	1-1/4X3/4X1-1/4	10	80	035	45.34
4101-156*	1-1/4X1X1/2	10	80	035	45.34
4101-157*	1-1/4X1X3/4	10	80	035	45.34
4101-158*	1-1/4X1X1	10	80	035	45.34
4101-159*	1-1/4X1X1-1/4	10	80	035	40.16
4101-166	1-1/4X1/2	10	120	035	41.37
4101-168	1-1/4X1-1/4X1	10	40	035	37.75
4101-167	1-1/4X3/4	10	80	035	41.37
4101-169*	1-1/4X1-1/4X1-1/2	5	40	035	56.35
4101-173*	1-1/2X1/2X1/2	5	40	035	56.35
4101-174*	1-1/2X1/2X3/4	5	40	035	56.35
4101-175*	1-1/2X1/2X1	5	40	035	56.35

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	Price Each
-------------	------	--------	----------	-----------	------------

REDUCING TEE (continued)

Socket x Socket x Socket

4101-176*	1-1/2X1/2X1-1/4	5	40	035	56.35
4101-177*	1-1/2X1/2X1-1/2	5	40	035	40.16
4101-182*	1-1/2X3/4X1/2	5	40	035	56.35
4101-184*	1-1/2X3/4X3/4	5	40	035	56.35
4101-185*	1-1/2X3/4X1	5	40	035	56.35
4101-186*	1-1/2X3/4X1-1/4	5	40	035	56.35
4101-188*	1-1/2X3/4X1-1/2	5	40	035	40.16
4101-193*	1-1/2X1X1/2	5	40	035	56.35
4101-194*	1-1/2X1X3/4	5	40	035	56.35
4101-195*	1-1/2X1X1	5	40	035	37.75
4101-196*	1-1/2X1X1-1/4	5	40	035	53.52
4101-197*	1-1/2X1X1-1/2	5	40	035	40.16
4101-199*	1-1/2X1-1/4X1/2	5	40	035	56.35
4101-201*	1-1/2X1-1/4X3/4	5	40	035	56.35
4101-202*	1-1/2X1-1/4X1	5	40	035	56.35
4101-203*	1-1/2X1-1/4X1-1/4	5	40	035	56.35
4101-204*	1-1/2X1-1/4X1-1/2	5	40	035	40.16
4101-209	1-1/2X1-1/2X1/2	25	0	035	40.16
4101-210	1-1/2X3/4	5	30	035	41.24
4101-211	1-1/2X1	10	30	035	56.35
4101-212*	1-1/2X1-1/2X1-1/4	5	40	035	40.16
4101-213*	1-1/2X1-1/2X2	5	0	035	99.16
4101-216*	2X1/2X1/2	5	0	035	99.16
4101-217*	2X1/2X3/4	5	0	035	99.16
4101-218*	2X1/2X1	5	0	035	99.16
4101-219*	2X1/2X1-1/4	5	0	035	99.16
4101-220*	2X1/2X1-1/2	5	0	035	99.16
4101-221*	2X1/2X2	5	0	035	79.19
4101-222*	2X3/4X1/2	5	0	035	99.16
4101-223*	2X3/4X3/4	5	0	035	99.16
4101-224*	2X3/4X1	5	0	035	99.16
4101-225*	2X3/4X1-1/4	5	0	035	99.16
4101-226*	2X3/4X1-1/2	5	0	035	99.16
4101-227*	2X3/4X2	5	0	035	79.19
4101-228*	2X1X1/2	5	0	035	99.16
4101-229*	2X1X3/4	5	0	035	99.16
4101-230*	2X1X1	5	0	035	99.16
4101-231*	2X1X1-1/4	5	0	035	99.16
4101-232*	2X1X1-1/2	5	0	035	99.16
4101-233*	2X1X2	5	0	035	79.19
4101-234*	2X1-1/4X1/2	5	0	035	99.16
4101-235*	2X1-1/4X3/4	5	0	035	99.16
4101-236*	2X1-1/4X1	5	0	035	99.16
4101-237*	2X1-1/2X1/2	5	0	035	99.16
4101-238*	2X1-1/2X3/4	5	0	035	99.16
4101-239*	2X1-1/2X1	5	0	035	99.16
4101-240*	2X1-1/2X1-1/4	5	0	035	99.16
4101-241*	2X1-1/2X1-1/2	5	0	035	99.16
4101-242*	2X1-1/4X1-1/4	5	0	035	99.16
4101-243*	2X1-1/4X1-1/2	5	0	035	99.16
4101-244*	2X1-1/4X2	5	0	035	79.19
4101-247	2X2X1/2	10	0	035	58.49

CTS CPVC Hot & Cold Water Distribution System
EverTUFF® CPVC CTS Fittings, Valves, Pipe & Cement

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	Price Each
-------------	------	--------	----------	-----------	------------

REDUCING TEE (continued)

Socket x Socket x Socket

4101-248	2X3/4	10	0	035	52.37
4101-249	2X2X1	5	15	035	49.62
4101-250*	2X2X1-1/4	5	0	035	49.62
4101-251	2X2X1-1/2	5	15	035	52.95
4101-257*	2X1-1/2X2	5	0	035	52.95

* Outlet sized with bushing.



90° ELL

Socket x Socket

4106-005	1/2	25	600	035	1.21
4106-007	3/4	25	300	035	2.00
4106-010	1	10	150	035	5.84
4106-012	1-1/4	10	80	035	11.63
4106-015	1-1/2	10	80	035	20.99
4106-020	2	5	30	035	40.25

REDUCING 90° ELL

Socket x Socket



4106-101	3/4X1/2	25	300	035	4.21
4106-130*	1X1/2	25	200	035	14.81
4106-131*	1X3/4	25	200	035	14.81
4106-167*	1-1/4X3/4	10	80	035	22.80
4106-168*	1-1/4X1	10	80	035	22.80
4106-209*	1-1/2X1/2	10	0	035	31.58
4106-210*	1-1/2X3/4	10	0	035	31.58
4106-211*	1-1/2X1	10	0	035	31.58
4106-212*	1-1/2X1-1/4	10	0	035	31.58
4106-247*	2X1/2	5	30	035	70.16
4106-248*	2X3/4	5	30	035	70.16
4106-249*	2X1	5	30	035	70.16
4106-250*	2X1-1/4	5	30	035	70.16
4106-251*	2X1-1/2	5	30	035	70.16

* Outlet sized with bushing.

90° EII - CTS Special Reinforced

Socket x SR Fipt - Stainless Steel Collar



4107-005SR	1/2	50	300	035	9.01
------------	-----	----	-----	-----	------

Drop Ear 90° EII - CTS Zinc Reinforced(One Piece Unit)

Socket x SR Fipt - Zinc Collar



DEZ4107-005SR	1/2	10	150	035	20.26
---------------	-----	----	-----	-----	-------

DROP EAR 90° ELL (Fitting with Bracket)

Socket x Socket



DE4106-005	1/2	25	150	035	3.62
------------	-----	----	-----	-----	------

DROP EAR BRACKET ONLY

For 4101-005 and 4106-005



DES-005	1/2	800	0	035	6.17
---------	-----	-----	---	-----	------

Drop Ear 90° EII - CTS Special Reinforced (Fitting Plus Bracket)

Socket x SR Fipt - Stainless Steel Collar



DE4107-005SR	1/2	10	200	035	13.93
--------------	-----	----	-----	-----	-------

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	Price Each
-------------	------	--------	----------	-----------	------------

DROP EAR BRACKET ONLY

For 4107-005SR



DET-005	1/2	400	0	035	6.17
---------	-----	-----	---	-----	------

90° STREET ELL

Spigot x Socket



4109-005	1/2	25	500	035	1.43
4109-007	3/4	25	300	035	2.24
4109-010	1	10	100	035	10.25

45° ELL

Socket x Socket



4117-005	1/2	25	500	035	1.54
4117-007	3/4	25	300	035	2.66
4117-010	1	10	100	035	6.77
4117-012	1-1/4	10	120	035	14.34
4117-015	1-1/2	10	80	035	20.78
4117-020	2	10	0	035	43.51

45° STREET ELL

Spigot x Socket



4127-005	1/2	25	600	035	3.26
4127-007	3/4	25	400	035	4.37
4127-010	1	10	150	035	12.56

COUPLING

Socket x Socket



4129-005	1/2	25	600	035	1.00
4129-007	3/4	25	300	035	1.32
4129-010	1	10	250	035	5.94
4129-012	1-1/4	10	120	035	7.67
4129-015	1-1/2	10	120	035	10.84
4129-020	2	10	0	035	20.64

REDUCER COUPLING

Socket x Socket



4129-101	3/4X1/2	25	300	035	2.12
4129-130	1X1/2	25	150	035	12.52
4129-131	1X3/4	25	150	035	6.78
4129-166*	1-1/4X1/2	10	120	035	15.69
4129-167*	1-1/4X3/4	10	120	035	15.69
4129-168*	1-1/4X1	10	120	035	22.33
4129-209*	1-1/2X1/2	10	80	035	21.28
4129-210*	1-1/2X3/4	10	60	035	21.28
4129-211*	1-1/2X1	10	60	035	21.28
4129-212*	1-1/2X1-1/4	10	80	035	21.28
4129-247*	2X1/2	10	0	035	46.09
4129-248*	2X3/4	10	0	035	46.09
4129-249*	2X1	10	0	035	46.09
4129-250*	2X1-1/4	10	0	035	46.09
4129-251*	2X1-1/2	10	0	035	46.09

* Outlet sized with bushing.

FEMALE ADAPTER with Gasket

Socket x NPSC



For Cold Water Service Only

4135-005OR	1/2	25	200	035	4.71
4135-007OR	3/4	25	300	035	6.68

CTS CPVC Hot & Cold Water Distribution System
EverTUFF® CPVC CTS Fittings, Valves, Pipe & Cement

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	Price Each
-------------	------	--------	----------	-----------	------------

FEMALE ADAPTER with Gasket (continued)

Socket x NPSC

4135-010OR	1	5	100	035	7.62
------------	---	---	-----	-----	------

Female Adapter - Gasket Sealed Brass Thread Transition

Socket x Gasket FPT - Use NO Thread Sealant

NSF Certified Lead Free

4135-005BRG	1/2	25	150	035	40.21
4135-007BRG	3/4	25	150	035	44.28
4135-010BRG	1	15	90	035	132.09
4135-012BRG	1-1/4	15	60	035	250.97
4135-015BRG	1-1/2	10	40	035	327.12
4135-020BRG	2	8	32	035	480.95



Female Adapter - Reducing Gasket Sealed Brass Thread Transition

Socket x Gasket FPT - Use NO Thread Sealant

NSF Certified Lead Free

4135-101BRG	3/4X1/2	25	150	035	43.77
4135-130BRG	1X1/2	50	0	035	69.15



Female Adapter - CTS Special Reinforced

Socket x SR Fipt - Stainless Steel Collar

4135-005SR	1/2	25	200	035	6.96
4135-007SR	3/4	25	300	035	7.65
4135-010SR	1	5	100	035	9.71



Female Adapter - CTS Reducing Special Reinforced

Socket x SR Fipt - Stainless Steel Collar

4135-131SR	1X3/4	25	150	035	15.28
------------	-------	----	-----	-----	-------



MALE ADAPTER

Mipt x Socket

For Cold Water Service Only

4136-005	1/2	25	600	035	1.26
4136-007	3/4	25	300	035	2.15
4136-010	1	10	250	035	10.16
4136-012	1-1/4	25	200	035	15.74
4136-015	1-1/2	10	80	035	19.41
4136-020	2	10	80	035	32.00



REDUCING MALE ADAPTER

Mipt x Socket

For Cold Water Service Only

4136-074	1/2X3/4	25	600	035	4.60
4136-101	3/4X1/2	25	600	035	4.93



MALE ADAPTER

Mipt x Spigot

For Cold Water Service Only

4161-005	1/2	50	700	035	3.91
----------	-----	----	-----	-----	------



Male Adapter - CTS Reinforce (Internal Stainless Steel Reinforced)

R Mipt x Socket - Stainless Steel Sleeve

4136-005R	1/2	25	300	035	8.93
4136-007R	3/4	25	300	035	9.93



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	Price Each
-------------	------	--------	----------	-----------	------------

Male Adapter - CTS Reinforce (Internal Stainless Steel Reinforced) (continued)

R Mipt x Socket - Stainless Steel Sleeve

4136-010R	1	10	120	035	14.79
-----------	---	----	-----	-----	-------

TRANSITION MALE ADAPTER w/BRASS THREAD

Brass Mipt x Socket

NSF Certified Lead Free

4136-005BR	1/2	60	360	035	40.21
4136-007BR	3/4	40	160	035	44.28
4136-010BR	1	10	60	035	132.09
4136-012BR	1-1/4	10	60	035	162.92
4136-015BR	1-1/2	10	40	035	215.06
4136-020BR	2	8	32	035	357.49



REDUCER BUSHING

Spigot x Socket

4137-101	3/4X1/2	25	600	035	1.51
4137-130	1X1/2	10	300	035	4.95
4137-131	1X3/4	10	400	035	4.95
4137-166	1-1/4X1/2	10	120	035	6.86
4137-167	1-1/4X3/4	10	300	035	6.42
4137-168	1-1/4X1	10	300	035	5.61
4137-209	1-1/2X1/2	25	100	035	8.07
4137-210	1-1/2X3/4	25	100	035	8.07
4137-211	1-1/2X1	10	120	035	7.92
4137-212	1-1/2X1-1/4	10	200	035	7.92
4137-247	2X1/2	10	60	035	19.16
4137-248	2X3/4	10	60	035	17.88
4137-249	2X1	10	60	035	17.88
4137-250	2X1-1/4	10	120	035	19.16
4137-251	2X1-1/2	10	120	035	17.88



TRANSITION BUSHING

IPS Spigot x CTS Socket

4140-005	1/2	10	600	035	6.40
4140-007	3/4	10	600	035	6.68
4140-010	1	10	400	035	7.38
4140-012	1-1/4	10	60	035	9.14
4140-015	1-1/2	10	60	035	11.52
4140-020	2	10	60	035	12.56



TRANSITION COUPLING

IPS Socket x CTS Socket

4141-007	3/4	25	300	035	4.36
4141-010	1	10	150	035	7.69



CAP Socket

4147-005	1/2	50	600	035	1.09
4147-007	3/4	25	300	035	1.39
4147-010	1	10	400	035	5.07
4147-012	1-1/4	10	120	035	6.97
4147-015	1-1/2	10	120	035	10.72
4147-020	2	10	80	035	21.63



CTS CPVC Hot & Cold Water Distribution System
EverTUFF® CPVC CTS Fittings, Valves, Pipe & Cement

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	Price Each
-------------	------	--------	----------	-----------	------------

UNION

Socket with EPDM O-ring Seal



100 psi Maximum Internal Pressure @ 180°F (82°C)

4197-005	1/2	25	150	035	14.25
4197-007	3/4	10	60	035	21.69
4197-010	1	10	60	035	28.00

Union - CTS Special Reinforced

Socket x SR Fipt - Stainless Steel Collar



100 psi Maximum Internal Pressure @ 180°F (82°C)

4199-005SR	1/2	20	120	035	21.25
4199-007SR	3/4	10	60	035	36.49
4199-010SR	1	10	40	035	43.76

Union - Gasket Sealed Brass Thread

Transition

Socket x Gasket FPT
 - Use No Thread Sealant



100 psi Maximum Internal Pressure @ 180°F (82°C)

NSF Certified Lead Free

4199-005BRG	1/2	20	120	035	45.31
4199-007BRG	3/4	10	0	035	52.70
4199-010BRG	1	10	40	035	68.13

1/4-Turn Angle Supply Stop

Socket x NPT



100 psi @ 180°F (82°C)

1/2" & 3/8" Male Thread for Connection to Female Flexible Supply Line

7722-005	1/2	50	400	217	4.00
7722-073	1/2X3/8	50	400	217	4.00

1/4-Turn Angle Supply Stop

SR FPT x NPT



100 psi @ 180°F (82°C)

1/2" & 3/8" Male Thread for Connection to Female Flexible Supply Line

7721-005SR	1/2	50	400	217	4.97
7721-073SR	1/2X3/8	50	400	217	4.97

CPVC CTS Ball Valves

Socket with EPDM O-ring Seal



100 psi Maximum Internal Pressure @ 180°F (82°C)

1922-005	1/2	50	200	217	33.39
1922-007	3/4	25	0	217	39.47
1922-010	1	25	0	217	45.53
1922-012	1-1/4	20	0	217	70.68
1922-015	1-1/2	20	0	217	101.94
1922-020	2	8	0	217	130.59

CPVC CTS Pipe - SDR 11

10' Lengths, Price Per Foot



List Price Per Foot

CTS-005	1/2	500	0	034	.98
CTS-007	3/4	250	0	034	1.76
CTS-010	1	150	0	034	3.61
CTS-012	1-1/4	100	0	034	5.35
CTS-015	1-1/2	100	0	034	7.10
CTS-020	2	50	0	034	12.01

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	Price Each
-------------	------	--------	----------	-----------	------------

CPVC CTS Pipe - SDR 11 (continued)

10' Lengths, Price Per Foot

- Pipe sold in bag quantities only - no broken bags
- No return on Pipe
- Large orders may be shipped directly from Spears® manufacturing facility. Note: Multiple drops may be made on TL shipments. Contact Spears® Regional Distribution Center for requirements and drop-off charges.
- See Spears® Manufacturing Company Terms and Conditions of Sale for freight requirements.

CPVC CTS PIPE WEIGHTS:

CTS-005 Weight per Foot .090 lbs; per Bag Weight 45 lbs.
CTS-007 Weight per Foot .149 lbs; per Bag Weight 37.25 lbs.
CTS-010 Weight per Foot .239 lbs; per Bag Weight 35.85 lbs.
CTS-012 Weight per Foot .353 lbs; per Bag Weight 35.3 lbs.
CTS-015 Weight per Foot .489 lbs; per Bag Weight 48.9 lbs.
CTS-020 Weight per Foot .810 lbs; per Bag Weight 40.5 lbs.

CPVC CTS Pipe - SDR 11

20' Lengths, Price Per Foot



List Price Per Foot

CTS-005-20	1/2	1000	0	034	.98
CTS-007-20	3/4	500	0	034	1.76
CTS-010-20	1	300	0	034	3.61
CTS-012-20	1-1/4	200	0	034	5.35
CTS-015-20	1-1/2	200	0	034	7.10
CTS-020-20	2	100	0	034	12.01

- Pipe sold in bag quantities only - no broken bags
- No return on Pipe
- Large orders may be shipped directly from Spears® manufacturing facility. Note: Multiple drops may be made on TL shipments. Contact Spears® Regional Distribution Center for requirements and drop-off charges.
- See Spears® Manufacturing Company Terms and Conditions of Sale for freight requirements.

CPVC CTS PIPE WEIGHTS:

CTS-005 Weight per Foot .090 lbs; per Bag Weight 90 lbs.
CTS-007 Weight per Foot .149 lbs; per Bag Weight 74.5 lbs.
CTS-010 Weight per Foot .239 lbs; per Bag Weight 71.7 lbs.
CTS-012 Weight per Foot .353 lbs; per Bag Weight 70.6 lbs.
CTS-015 Weight per Foot .489 lbs; per Bag Weight 97.8 lbs.
CTS-020 Weight per Foot .830 lbs; per Bag Weight 83 lbs.

CPVC CTS Coiled Pipe - SDR 11

100 ft. Coil, Price Per Foot



List Price Per Foot

CTS-005-100	1/2	100	0	034	1.15
CTS-007-100	3/4	100	0	034	2.09
CTS-010-100	1	100	0	034	4.11

- Pipe sold in coil quantities only - no broken coils
- No return on Coiled Pipe
- Large orders may be shipped directly from Spears® manufacturing facility. Note: Multiple drops may be made on TL shipments. Contact Spears® Regional Distribution Center for requirements and drop-off charges.
- See Spears® Manufacturing Company Terms and Conditions of Sale for freight requirements.

CPVC CTS COILED PIPE WEIGHTS:

CTS-005-100 Weight per Foot .090 lbs; per Coil Weight 9 lbs.
CTS-007-100 Weight per Foot .149 lbs; per Coil Weight 14.9 lbs.
CTS-010-100 Weight per Foot .239 lbs; per Coil Weight 23.9 lbs.

WARNING:

Banded coils will expand when opened. Exercise caution to avoid injury during banding removal.

CTS TUBING STRAPS

Std Pk Bag of 25 For Anchoring CTS Pipe



Sold in Full Bag Quantity Only

556A	1/2	25	500	901	.94
556B	3/4	25	500	901	.94

CTS CPVC Hot & Cold Water Distribution System
EverTUFF® CPVC CTS Fittings, Valves, Pipe & Cement

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	Price Each
-------------	------	--------	----------	-----------	------------

CTS TUBE TALON with NAIL

Std Pk Bag Quantities as Specified. For Anchoring CTS Pipe



Sold in Full Bag Quantity Only

555A	1/2	100	1000	901	1.04
555B	3/4	100	1000	901	1.58
555C	1	50	500	901	4.44

EverTUFF® CTS One Step CPVC Solvent Cement



CTS5-005	1/4 Pint	24	0	701	9.01
CTS5-010	1/2 Pint	24	0	701	14.34
CTS5-020	Pint	12	0	701	23.23
CTS5-030	Quart	12	0	701	40.42
CTS5-040	Gallon	6	0	701	138.29

Cap Daubers



DHP-38	3/8" for 1/2 Pint	50	400	710	1.23
DHP-50	1/2" for 1/2 Pint	50	400	710	1.23
DHP-75	3/4" for 1/2 Pint	50	0	710	1.31
DP-50	1/2" for Pint	50	0	710	1.23
DP-75	3/4" for Pint	50	0	710	1.31
DP-125	1-1/4" for Pint	50	0	710	1.58
DQ-50	1/2" for Quart	50	0	710	1.23
DQ-75	3/4" for Quart	50	0	710	1.23
DQ-125	1-1/4" for Quart	50	0	710	1.58

3/8" Diameter for pipe sizes to 3/4"
 1/2" Diameter for pipe sizes to 1"
 3/4" Diameter for pipe size to 1-1/2"
 1-1/4" Diameter for pipe size 1-1/2" to 3"

Can-Mate Daubers

Adjustable Plastic Applicator with Telescoping Stem for use with Standard 1/2 Pint, Pint and Quart Cans



CM-50	1/2"	50	0	710	5.26
CM-75	3/4"	50	0	710	5.26
CM-150	1-1/4"	50	0	710	5.26

1/2" Diameter for pipe sizes to 1"
 3/4" Diameter for pipe size to 1-1/2"
 1-1/4" Diameter for pipe size 1-1/2" to 3"

Deburring Tool

Cone Type for pipe from 1/2" through 2"



DEB-2	1/2 to 2 Pipe	1	6	710	97.71
-------	---------------	---	---	-----	-------