

Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------

PVC CEMENTS

PVC HEAVY DUTY CLEAR CEMENT

- Heavy-bodied clear cement for PVC pipe and fittings. Up to 12" diameter for Sch. 40 and Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water and DWV.
- Recommended application temperature 40°F to 110°F.
- Thick formula fill gaps in large diameter pipe and loose fitting joints.
- Meets ASTM D-2564.

30850	4 oz.	PVC Heavy Duty Clear	038753-308500	24	9
30863	8 oz.	PVC Heavy Duty Clear	038753-308630	24	16
308630	8 oz.	PVC Heavy Duty Clear - 40 Pack	038753-308630	40	16
30876	16 oz.	PVC Heavy Duty Clear	038753-308760	24	29
30876D	16 oz.	PVC Heavy Duty Clear - Display	038753-308760	24	29
31008	32 oz.	PVC Heavy Duty Clear	038753-310084	12	29
310086	32 oz.	PVC Heavy Duty Clear - 6 Pack	038753-310084	6	14.5
31011	Gallon	PVC Heavy Duty Clear - Wide Mouth Can	038753-310114	6	54



LO-V.O.C. PVC HEAVY DUTY CLEAR CEMENT • Meets California and other environmental district rules.

31850	4 oz.	LO-V.O.C. PVC Heavy Duty Clear	038753-318509	24	9
31851	8 oz.	LO-V.O.C. PVC Heavy Duty Clear	038753-318516	24	16
31852	16 oz.	LO-V.O.C. PVC Heavy Duty Clear	038753-318523	24	29
31853	32 oz.	LO-V.O.C. PVC Heavy Duty Clear	038753-318530	12	29



PVC MEDIUM CLEAR CEMENT

- Medium-bodied clear cement for use on PVC pipe and fittings. Up to 6" diameter for Sch. 40 and Sch. 80.
- Recommended application temperature 40°F to 110°F.
- Recommended for all grades and types of PVC pipe and fittings, drain, waste, vent pipe, and potable water.
- Meets ASTM D-2564.

31017	4 oz.	PVC Medium Clear	038753-310176	24	9
31017D	4 oz.	PVC Medium Clear - Display	038753-310176	72	9
31018	8 oz.	PVC Medium Clear	038753-310183	24	15
310180	8 oz.	PVC Medium Clear - 40 Pack	038753-310183	40	16
31019	16 oz.	PVC Medium Clear	038753-310190	24	28
31019D	16 oz.	PVC Medium Clear - Display	038753-310190	24	28
31020	32 oz.	PVC Medium Clear	038753-310206	12	27
310206	32 oz.	PVC Medium Clear - 6 Pack	038753-310206	6	40
31021	Gallon	PVC Medium Clear	038753-310213	6	50



LO-V.O.C. PVC MEDIUM CLEAR CEMENT • Meets California and other environmental district rules.

31845	4 oz.	LO-V.O.C. PVC Medium Clear	038753-318455	24	9
31845D	4 oz.	LO-V.O.C. PVC Medium Clear - Display	038753-318455	72	9
31846	8 oz.	LO-V.O.C. PVC Medium Clear	038753-318462	24	15
31847	16 oz.	LO-V.O.C. PVC Medium Clear	038753-318479	24	28
31847D	16 oz.	LO-V.O.C. PVC Medium Clear - Display	038753-318479	24	28
318460	16 oz.	LO-V.O.C. PVC Medium Clear - 40 Pack	038753-318462	40	25
31848	32 oz.	LO-V.O.C. PVC Medium Clear	038753-318486	12	27
318486	32 oz.	LO-V.O.C. PVC Medium Clear - 6 Pack	038753-318486	6	27
31849	Gallon	LO-V.O.C. PVC Medium Clear	038753-318493	6	50



PVC REGULAR CLEAR CEMENT

- Regular-bodied clear cement for use on PVC pipe and fittings. Up to 4" for DWV Sch. 40 and up to 2" for Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water and DWV.
- Sets up quickly.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

31012	4 oz.	PVC Regular Clear	038753-310121	24	8
31012D	4 oz.	PVC Regular Clear - Display	038753-310121	72	8
31013	8 oz.	PVC Regular Clear	038753-310138	24	15
310131	8 oz.	PVC Regular Clear - 40 Pack	038753-310138	40	16
31014	16 oz.	PVC Regular Clear	038753-310145	24	28
31014D	16 oz.	PVC Regular Clear - Display	038753-310145	24	28
31015	32 oz.	PVC Regular Clear	038753-310152	12	27
31016	Gallon	PVC Regular Clear	038753-310169	6	50





Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
LO-V.O.C. PVC REGULAR CLEAR CEMENT • Meets California and other environmental district rules.					
31840	4 oz.	LO-V.O.C. PVC Regular Clear	038753-318400	24	8
31841	8 oz.	LO-V.O.C. PVC Regular Clear	038753-318417	24	15
318411	8 oz.	LO-V.O.C. PVC Regular Clear - 40 Pack	038753-318417	40	25
31842	16 oz.	LO-V.O.C. PVC Regular Clear	038753-318424	24	28
31842D	16 oz.	LO-V.O.C. PVC Regular Clear - Display	038753-318424	24	28
31843	32 oz.	LO-V.O.C. PVC Regular Clear	038753-318431	12	27
31844	Gallon	LO-V.O.C. PVC Regular Clear	038753-318448	6	50



PVC REGULAR CLEAR ADVANCED CEMENT					
<ul style="list-style-type: none"> Regular-bodied clear cement for use on PVC pipe and fittings. Up to 4" for DWV Sch. 40 and up to 2" for Sch. 80. Recommended for ALL grades and types of PVC pipe and fittings, potable water and DWV. Sets up quickly. Recommended application temperature 40°F to 110°F. Meets ASTM D-2564. 					
31925	4 oz.	PVC Regular Clear Advanced	038753-319254	24	8
31926	8 oz.	PVC Regular Clear Advanced	038753-319261	24	15
31927	16 oz.	PVC Regular Clear Advanced	038753-319278	24	28
31928	32 oz.	PVC Regular Clear Advanced	038753-319285	12	27
31929	Gallon	PVC Regular Clear Advanced	038753-319292	6	50



PVC HEAVY DUTY GRAY CEMENT					
<ul style="list-style-type: none"> Heavy-bodied gray colored cement for use on PVC pipe and fittings. Up to 12" diameter for Sch. 40 and Sch. 80. Recommended for ALL grades and types of PVC pipe and fittings, potable water and DWV. Thick formula fills gaps in large diameter pipe and fittings. Recommended application temperature 40°F to 110°F. Meets ASTM D-2564. 					
31093	4 oz.	PVC Heavy Duty Gray	038753-310930	24	9
31094	8 oz.	PVC Heavy Duty Gray	038753-310947	24	16
31095	16 oz.	PVC Heavy Duty Gray	038753-310954	24	31
31105	32 oz.	PVC Heavy Duty Gray	038753-311050	12	29
31118	Gallon	PVC Heavy Duty Gray - Wide Mouth Can	038753-311180	6	54



LO-V.O.C. PVC HEAVY DUTY GRAY CEMENT • Meets California and other environmental district rules.					
31860	4 oz.	LO-V.O.C. PVC Heavy Duty Gray	038753-318608	24	9
31861	8 oz.	LO-V.O.C. PVC Heavy Duty Gray	038753-318615	24	15
31862	16 oz.	LO-V.O.C. PVC Heavy Duty Gray	038753-318622	24	31
31863	32 oz.	LO-V.O.C. PVC Heavy Duty Gray	038753-318639	12	29
318636	32 oz.	LO-V.O.C. PVC Heavy Duty Gray - 6 Pack	038753-318639	6	14
31864	Gallon	LO-V.O.C. PVC Heavy Duty Gray	038753-318646	6	51



PVC HEAVY DUTY GRAY FAST SET CEMENT					
<ul style="list-style-type: none"> Very heavy-bodied medium-setting gray colored cement for use on PVC pipe and fittings. Up to 18" diameter for Sch. 40 and Sch. 80. Formulated for quick installation of irrigation pipe and fittings. Recommended for ALL grades and types of PVC pipe and fittings, potable water and DWV. Builds up for large diameter installations. Fill gaps in large diameter pipe and loose fitting joints. Recommended application temperature 40°F to 110°F. Meets ASTM D-2564. 					
31121	16 oz.	PVC Heavy Duty Gray Fast Set	038753-311210	24	27
31122	32 oz.	PVC Heavy Duty Gray Fast Set	038753-311227	12	28
31123	Gallon	PVC Heavy Duty Gray Fast Set Wide Mouth Can	038753-311234	6	50



LO-V.O.C. PVC HEAVY DUTY GRAY CEMENT - INDUSTRIAL GRADE					
<ul style="list-style-type: none"> Heavy bodied cement for use on pressure industrial systems, drain, waste and vent pipe. No special techniques required. Resistant to caustics and hypochlorites up to 15% solution. INDUSTRIAL GRADE. For Sch. 40 and Sch. 80 PVC, Types I and II up to 12" diameter. Meets ASTM D-2564. 					
31113	16 oz.	LO-V.O.C. PVC Heavy Duty Gray	038753-311135	24	30
31114	32 oz.	LO-V.O.C. PVC Heavy Duty Gray	038753-311142	12	29
31115	Gallon	LO-V.O.C. PVC Heavy Duty Gray - Wide Mouth Can	038753-311159	6	50

Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------

PVC MEDIUM GRAY CEMENT

- Medium-bodied gray colored cement for use on PVC pipe and fittings. Up to 6" diameter for Sch. 40 and Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water and DWV.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

30883	4 oz.	PVC Medium Gray	038753-308838	24	9
30883D	4 oz.	PVC Medium Gray - Display	038753-308838	72	9
30884	8 oz.	PVC Medium Gray	038753-308845	24	15
30885	16 oz.	PVC Medium Gray	038753-308852	24	29
30886	32 oz.	PVC Medium Gray	038753-308869	12	28
30887	Gallon	PVC Medium Gray	038753-308876	6	50



LO-V.O.C. PVC MEDIUM GRAY CEMENT • Meets California and other environmental district rules.

31865	4 oz.	LO-V.O.C. PVC Medium Gray	038753-318653	24	9
31865D	4 oz.	LO-V.O.C. PVC Medium Gray - Display	038753-318653	72	27
31866	8 oz.	LO-V.O.C. PVC Medium Gray	038753-318660	24	15
31867	16 oz.	LO-V.O.C. PVC Medium Gray	038753-318677	24	29
31868	32 oz.	LO-V.O.C. PVC Medium Gray	038753-318684	12	28
31869	Gallon	LO-V.O.C. PVC Medium Gray	038753-318691	6	50



PVC RAIN-R-SHINE® BLUE CEMENT

- Medium-bodied blue colored cement for PVC pipe and fittings. Up to 6" diameter.
- Very fast-setting cement formulated for wet conditions and/or quick pressurization and fast installation.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water and DWV.
- Both Sch. 40 and Sch. 80.
- Pool/Irrigation.
- Recommended application temperature 40°F to 110°F.
- No primer needed on non-pressure DWV, up to 4" where local codes permit.
- Meets ASTM D-2564.

30890	4 oz.	PVC Rain-R-Shine® Blue	038753-308906	24	9
30891	8 oz.	PVC Rain-R-Shine® Blue	038753-308913	24	16
308910	8 oz.	PVC Rain-R-Shine® Blue - 40 Pack	038753-308913	40	26
30893	16 oz.	PVC Rain-R-Shine® Blue	038753-308937	24	28
30893D	16 oz.	PVC Rain-R-Shine® Blue - Display	038753-308937	24	28
30894	32 oz.	PVC Rain-R-Shine® Blue	038753-308944	12	28
308946	32 oz.	PVC Rain-R-Shine® Blue - 6 Pack	038753-308944	6	14
30895	Gallon	PVC Rain-R-Shine® Blue - Wide Mouth Can	038753-308951	6	50



LO-V.O.C. PVC RAIN-R-SHINE® BLUE CEMENT • Meets California and other environmental district rules.

31855	4 oz.	LO-V.O.C. PVC Rain-R-Shine® Blue	038753-318554	24	9
31856	8 oz.	LO-V.O.C. PVC Rain-R-Shine® Blue	038753-318561	24	16
318560	8 oz.	LO-V.O.C. PVC Rain-R-Shine® Blue - 40 Pack	038753-318561	40	26
31857	16 oz.	LO-V.O.C. PVC Rain-R-Shine® Blue	038753-318578	24	28
31857D	16 oz.	LO-V.O.C. PVC Rain-R-Shine® Blue - Display	038753-318578	24	28
31858	32 oz.	LO-V.O.C. PVC Rain-R-Shine® Blue	038753-318585	12	28
31859	Gallon	LO-V.O.C. PVC Rain-R-Shine® Blue	038753-318592	6	50



PVC ALL WEATHER CLEAR CEMENT

- Medium-bodied clear cement for use on PVC pipe and fittings. Up to 6" diameter.
- Meets ASTM D-2564.
- No primer needed on non-pressure DWV, up to 4" where local codes permit.
- Recommended for all grades and types of PVC pipe and fittings, potable water and DWV, Sch. 40 and Sch. 80.
- Recommended application temperature of -15°F to 110°F.

31132	16 oz.	PVC All Weather Clear	038753-311326	24	30
31132D	16 oz.	PVC All Weather Clear - Display	038753-311326	24	30
31133	32 oz.	PVC All Weather Clear	038753-311333	12	29
31135	Gallon	PVC All Weather Clear - Wide Mouth Can	038753-311357	6	50



Product No.	Size	Description	UPC Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	----------	-----------------	----------

ALL PURPOSE CEMENT



- Medium-bodied milky clear cement for ABS, PVC, or CPVC up to 6" diameter.
- Recommended for pipe and fittings Sch. 40 and Sch. 80, potable water and DWV.
- Recommended application temperature 40°F to 110°F.
- Meets performance requirements of ASTM D-2564, D-2235, F-493.
- Check local codes for acceptability of this product.

30818	4 oz.	All Purpose Cement	038753-308180	24	9
30818D	4 oz.	All Purpose Cement - Display	038753-308180	72	27
30821	8 oz.	All Purpose Cement	038753-308210	24	16
308210	8 oz.	All Purpose Cement - 40 Pack	038753308210	40	26
30834	16 oz.	All Purpose Cement	038753-308340	24	29
30834D	16 oz.	All Purpose Cement - Display	038753-308340	24	24
30847	32 oz.	All Purpose Cement	038753-308470	12	29
30848	Gallon	All Purpose Cement	038753-308487	6	50



LO-V.O.C. ALL PURPOSE CEMENT • Meets California and other environmental district rules.

31895	4 oz.	LO-V.O.C. All Purpose	038753-318950	24	9
31896	8 oz.	LO-V.O.C. All Purpose	038753-318967	24	15



PVC FLEXIBLE CLEAR CEMENT

- Medium-bodied clear cement for use on flexible PVC pipe and rigid fittings. Up to 3" diameter.
- Formulated to withstand pressures and vibrations commonly associated with spa and swimming pool installations.
- Meets manufacturer's rated line pressure for flexible PVC pipe.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

30875	4 oz.	PVC Flexible Clear	038753-308753	12	4
30879	32 oz.	PVC Flexible Clear	038753-308791	12	28



ABS TO PVC TRANSITION GREEN CEMENT

- Medium-bodied green colored cement for use in joining ABS to PVC in non-pressure transition joints.
- All schedules up to 6" diameter pipe and fittings.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-3138.

30900	4 oz.	ABS To PVC Transition Green	038753-309002	24	6
30925	16 oz.	ABS To PVC Transition Green	038753-309255	6	7
30926	32 oz.	ABS To PVC Transition Green	038753-309262	12	28



LO-V.O.C. ABS TO PVC TRANSITION GREEN CEMENT

- Meets California and other environmental district rules.

31807	16 oz.	LO-V.O.C. ABS To PVC Transition Green	038753-318073	6	7
31808	32 oz.	LO-V.O.C. ABS To PVC Transition Green	038753-318080	12	23



HANDY PACKS

- Convenient "Handy Pack" for storage – just add pipe and fittings.
- Contains one can of PVC Cement and one can of Primer.



30238	4 oz.	LO-V.O.C. PVC Regular & NSF Purple Primer	038753-302386	12	9
30242	8 oz.	LO-V.O.C. PVC Medium & NSF Purple Primer	038753-302423	20	28
30246	4 oz.	PVC Regular & NSF Purple Primer	038753-302461	12	9
30246D	4 oz.	PVC Regular & NSF Purple Primer - Display	038753-302461	24	18
302480	8 oz.	PVC Regular & NSF Purple Primer - Mini	038753-302485	160	224
30244	8 oz.	PVC Medium & NSF Purple Primer	038753-302447	20	26
30247	8 oz.	LO-V.O.C. PVC Regular & NSF Purple Primer	038753-302478	20	26



Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------

ABS CEMENTS

ABS BLACK CEMENT

- Medium-bodied black cement for ABS pipe and fittings. Up to 6" diameter.
- For ALL types and grades of ABS pipe and fittings for DWV.
- For all non-pressure applications.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2235.

30999	4 oz.	ABS Black	038753-309996	24	8
30999D	4 oz.	ABS Black - Display	038753-309996	48	16
30889	8 oz.	ABS Black	038753-308890	24	15
308890	8 oz.	ABS Black - 40 Pack	038753-308890	40	25
30892	16 oz.	ABS Black	038753-308920	24	28
30892D	16 oz.	ABS Black - Display	038753-308920	24	28
30902	32 oz.	ABS Black	038753-309026	12	26
309026	32 oz.	ABS Black - 6 Pack	038753-309026	6	13
30915	Gallon	ABS Black	038753-309156	6	51



LO-V.O.C. ABS BLACK CEMENT • Meets California and other environmental district rules.

31800	4 oz.	LO-V.O.C. ABS Black	038753-318004	24	8
31800D	4 oz.	LO-V.O.C. ABS Black - Display	038753-318004	72	27
31801	8 oz.	LO-V.O.C. ABS Black	038753-318011	24	15
318011	8 oz.	LO-V.O.C. ABS Black - 40 Pack	038753-318011	40	25
31802	16 oz.	LO-V.O.C. ABS Black	038753-318028	24	28
31803	32 oz.	LO-V.O.C. ABS Black	038753-318035	12	26
318036	32 oz.	LO-V.O.C. ABS Black - 6 Pack	038753-318035	6	13
31804	Gallon	LO-V.O.C. ABS Black	038753-318042	6	51



ABS SPECIAL MILKY CLEAR CEMENT

- For ALL types and grades of ABS pipe and fittings for DWV.
- Fast curing for all non-pressure applications.
- Formulated to eliminate the clean-up problems associated with black ABS cements.
- Medium-bodied milky clear cement for ABS pipe and fittings. Up to 6" diameter.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2235.

30922	16 oz.	ABS Special Milky Clear	038753-309224	24	28
30923	32 oz.	ABS Special Milky Clear	038753-309231	12	27
30924	Gallon	ABS Special Milky Clear	038753-309248	6	51



LO-V.O.C. ABS MILKY CLEAR CEMENT • Meets California and other environmental district rules.

31908	32 oz.	LO-V.O.C. ABS Milky Clear	038753-319087	12	27
-------	--------	---------------------------	---------------	----	----



ABS EXTRA SPECIAL BLACK CEMENT

- Medium-bodied black cement for use on ABS pipe and fittings. Up to 6" diameter.
- Formulated especially for the hot, arid climates in the Western states.
- For all non-pressure applications.
- For ALL types and grades of ABS pipe and fittings for DWV.
- Meets ASTM D-2235.

30916	4 oz.	ABS Extra Special Black	038753-309163	24	9
30916D	4 oz.	ABS Extra Special Black - Display	038753-309163	72	27
30917	8 oz.	ABS Extra Special Black	038753-309170	24	15
309170	8 oz.	ABS Extra Special Black - 40 Pack	038753-309170	40	25
30918	16 oz.	ABS Extra Special Black	038753-309187	24	28
30919	32 oz.	ABS Extra Special Black	038753-309194	12	27
30920	Gallon	ABS Extra Special Black	038753-309200	6	51



Product No.	Size	Description	UPC Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	----------	-----------------	----------

CPVC CEMENTS



CPVC HEAVY DUTY GRAY CEMENT

- Heavy-bodied gray colored cement for use on CPVC pipe and fittings up to 12" diameter.
- For C.T.S. (copper tube size) and Sch. 80, potable water pressure pipe.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM F-493.

31036	16 oz.	CPVC Heavy Duty Gray	038753-310367	24	29
31037	32 oz.	CPVC Heavy Duty Gray	038753-310374	12	29



LO-V.O.C. CPVC HEAVY DUTY GRAY CEMENT - INDUSTRIAL GRADE

- Heavy-bodied cement for use on pressure industrial systems, drain, waste and vent pipe.
- Resistant to caustics and hypochlorites up to 15% solution.
- For Sch. 40 and Sch. 80 CPVC, Type IV up to 12" diameter.
- No special techniques required.
- INDUSTRIAL GRADE.
- Meets ASTM F-493.

31148	16 oz.	LO-V.O.C. CPVC Heavy Duty Gray	038753-311487	24	30
31149	32 oz.	LO-V.O.C. CPVC Heavy Duty Gray	038753-311494	12	29
31150	Gallon	LO-V.O.C. CPVC Heavy Duty Gray - Wide Mouth Can	038753-311500	6	50



CPVC MEDIUM ORANGE CEMENT

- Medium-bodied orange colored cement for use on CPVC pipe and fittings. Up to 6" diameter.
- For C.T.S. (copper tube size) and Sch. 80, potable water pressure pipe.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM F-493.

31128	4 oz.	CPVC Medium Orange	038753-311289	24	9
31128D	4 oz.	CPVC Medium Orange - Display	038753-311289	72	27
31129	8 oz.	CPVC Medium Orange	038753-311296	24	16
311290	8 oz.	CPVC Medium Orange - 40 Pack	038753-311296	40	26
31130	16 oz.	CPVC Medium Orange	038753-311302	24	29
31131	32 oz.	CPVC Medium Orange	038753-311319	12	29
31127	Gallon	CPVC Medium Orange	038753-311272	6	51



LO-V.O.C. CPVC MEDIUM ORANGE CEMENT • Meets California and other environmental district rules.

31820	4 oz.	LO-V.O.C. CPVC Medium Orange	038753-318202	24	9
31820D	4 oz.	LO-V.O.C. CPVC Medium Orange	038753-318202	72	27
31821	8 oz.	LO-V.O.C. CPVC Medium Orange	038753-318219	24	16
318210	8 oz.	LO-V.O.C. CPVC Medium Orange	038753-318219	24	16
31822	16 oz.	LO-V.O.C. CPVC Medium Orange	038753-318226	24	29



LO-V.O.C. CPVC FLOWGUARD GOLD** ALL WEATHER 1-STEP YELLOW CEMENT

- Exceeds new environmental requirements and meets various California district rules.
- May be used without primer where local codes permit.
- For cold water systems and hot water systems up to 180°F.
- Faster cure time/reduced installation time.
- For copper tube size (CTS) CPVC hot and cold potable water pipe and fittings up to 2" diameter interference fit only.
- Meets ASTM F-493.

31910	4 oz.	LO-V.O.C. CPVC Flowguard Gold® 1-Step Yellow	038753-319100	24	9
31911	8 oz.	LO-V.O.C. CPVC Flowguard Gold® 1-Step Yellow	038753-319117	24	16
319110	8 oz.	LO-V.O.C. CPVC Flowguard Gold® 1-Step Yellow - 40 Pack	038753-319117	40	26
31912	16 oz.	LO-V.O.C. CPVC Flowguard Gold® 1-Step Yellow	038753-319124	24	29
31913	32 oz.	LO-V.O.C. CPVC Flowguard Gold® 1-Step Yellow	038753-319131	12	29
31914	Gallon	LO-V.O.C. CPVC Flowguard Gold® 1-Step Yellow	038753-319148	6	54

*FlowGuard Gold is a registered trademark of the Lubrizol Corporation.

Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------

PRIMERS & CLEANERS

PURPLE PRIMER - NSF LISTED

- Purple-tinted aggressive primer for use on PVC and CPVC pipe and fittings.
- Removes surface dirt, grease and grime as well as softens the pipe surface to allow a fast, secure solvent weld.
- For use in areas where plumbing code calls for verification that a primer has been used.
- Meets ASTM F-656.

30755	4 oz.	Purple Primer - NSF Listed	038753-307558	24	8
30755D	4 oz.	Purple Primer - NSF Listed - Display	038753-307558	72	8
30756	8 oz.	Purple Primer - NSF Listed	038753-307565	24	14
307560	8 oz.	Purple Primer - NSF Listed - 40 Pack	038753-307565	40	23
30757	16 oz.	Purple Primer - NSF Listed	038753-307572	24	25
30757D	16 oz.	Purple Primer - NSF Listed - Display	038753-307572	24	25
30758	32 oz.	Purple Primer - NSF Listed	038753-307589	12	24
307586	32 oz.	Purple Primer - NSF Listed - 6 Per	038753-307589	6	24
30759	Gallon	Purple Primer - NSF Listed	038753-307596	6	45



LO-V.O.C. PURPLE PRIMER - NSF LISTED • Meets California and other environmental district rules.

31900	4 oz.	LO-V.O.C. Purple Primer - NSF Listed	038753-319001	24	8
31900D	4 oz.	LO-V.O.C. Purple Primer - NSF Listed - Display	038753-319001	72	24
31901	8 oz.	LO-V.O.C. Purple Primer - NSF Listed	038753-319018	24	14
319010	8 oz.	LO-V.O.C. Purple Primer - NSF Listed - 40 Pack	038753-319018	40	27
31902	16 oz.	LO-V.O.C. Purple Primer - NSF Listed	038753-319025	24	25
31902D	16 oz.	LO-V.O.C. Purple Primer - NSF Listed	038753-319025	24	25
31903	32 oz.	LO-V.O.C. Purple Primer - NSF Listed	038753-319032	12	24
319036	32 oz.	LO-V.O.C. Purple Primer - NSF Listed - 6 Pack	038753-319032	6	12
31904	Gallon	LO-V.O.C. Purple Primer - NSF Listed	038753-319049	6	45



CLEAR PRIMER - NSF LISTED

- A clear aggressive primer for use on PVC and CPVC pipe and fittings.
- All schedules and all diameters.
- Removes all surface dirt, grease and grime as well as softens pipe in preparation for solvent cement.
- Meets ASTM F-656.

30750	4 oz.	Clear Primer - NSF Listed	038753-307503	24	8
30751	8 oz.	Clear Primer - NSF Listed	038753-307510	24	14
30752	16 oz.	Clear Primer - NSF Listed	038753-307527	24	25
30753	32 oz.	Clear Primer - NSF Listed	038753-307534	12	24
30754	Gallon	Clear Primer - NSF Listed	038753-307541	6	46



PURPLE PRIMER/CLEANER

- Purple-tinted all purpose primer/cleaner for PVC and CPVC pipe and fittings.
- Less aggressive than clear primer and purple primer.
- Removes surface dirt, grease and grime as well as softens pipe in preparation for solvent cement.

30780	4 oz.	Purple Primer/Cleaner	038753-307800	24	8
30780D	4 oz.	Purple Primer/Cleaner - Display	038753-307800	72	24
30783	8 oz.	Purple Primer/Cleaner	038753-307831	24	14
307830	8 oz.	Purple Primer/Cleaner - 40 Pack	038753-307831	40	23
30796	16 oz.	Purple Primer/Cleaner	038753-307961	24	25
30806	32 oz.	Purple Primer/Cleaner	038753-308067	12	24
30768	Gallon	Purple Primer/Cleaner	038753-307688	6	46



CLEANER

- Clear cleaner for ABS, PVC and CPVC pipe and fittings.
- All schedules and all diameters.
- Flows freely and evaporates quickly.
- Fast-acting cleaner removes surface dirt, grease and grime.

30779	4 oz.	Clear Cleaner	038753-307794	24	8
30779D	4 oz.	Clear Cleaner - Display	038753-307794	72	24
30782	8 oz.	Clear Cleaner	038753-307824	24	14
307820	8 oz.	Clear Cleaner - 40 Pack	038753-307824	40	23
30795	16 oz.	Clear Cleaner	038753-307954	24	26
30805	32 oz.	Clear Cleaner	038753-308050	12	25
308056	32 oz.	Clear Cleaner - 6 Pack	038753-308050	6	12
30766	Gallon	Clear Cleaner - Wide Mouth Cleaner	038753-307664	6	46



Product No.	Size	Description	UPC Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	----------	-----------------	----------

UNITED ELCHEM PVC CEMENTS



PLUMB-TITE™ PVC MEDIUM "HOT" BLUE CEMENT

- Medium-bodied blue colored cement for PVC pipe and fittings Up to 6" diameter.
- Very fast setting cement formulated for wet conditions and/or quick pressurization and fast installation.
- Recommended for ALL grades and types of PVC pipe and fittings potable water, pressure pipe and DWV.
- Fades to clear in sunlight.
- No primer needed on non-pressure DWV up to 4" diameter, where local codes permit.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

2066S	4 oz.	Plumb-Tite PVC Medium "Hot" Blue	083675-020665	24	9
2056S	8 oz.	Plumb-Tite PVC Medium "Hot" Blue	083675-020566	24	16
2046S	16 oz.	Plumb-Tite PVC Medium "Hot" Blue	083675-020467	24	27
2036S	32 oz.	Plumb-Tite PVC Medium "Hot" Blue	083675-020368	12	26
2024	Gallon	Plumb-Tite PVC Medium "Hot" Blue	083675-020245	6	52



PLUMB-TITE™ LOW-V.O.C. PVC MEDIUM "HOT" BLUE CEMENT

- Meets California and other environmental district rules.

200166S	4 oz.	Plumb-Tite PVC Medium "Hot" Blue	083675-220159	24	9
200136S	32 oz.	Plumb-Tite PVC Medium "Hot" Blue	083675-220128	12	26
200124C	Gallon	Plumb-Tite PVC Medium "Hot" Blue	083675-220111	6	52



TURF-TITE™ PVC MEDIUM "HOT" BLUE CEMENT

- Medium-bodied blue colored cement for PVC pipe and fittings Up to 6" diameter.
- Very fast setting cement formulated for wet conditions and/or quick pressurization and fast installation.
- Recommended for ALL grades and types of PVC pipe and fittings potable water, pressure pipe and DWV.
- Fades to clear in sunlight.
- No primer needed on non-pressure DWV up to 4" diameter, where local codes permit.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

2466S	4 oz.	Turf-Tite PVC Medium "Hot" Blue	083675-024663	24	9
2456S	8 oz.	Turf-Tite PVC Medium "Hot" Blue	083675-024564	24	16
2446S	16 oz.	Turf-Tite PVC Medium "Hot" Blue	083675-024465	24	27
2436S	32 oz.	Turf-Tite PVC Medium "Hot" Blue	083675-024366	12	26
2424	Gallon	Turf-Tite PVC Medium "Hot" Blue	083675-024243	6	52



LOW - V.O.C. TURF-TITE™ PVC MEDIUM "HOT" BLUE CEMENT

- Meets California environmental district rules.

240156S	8 oz.	Low - VOC Turf-Tite Medium "Hot" Blue	083675-240148	24	16
240146S	16 oz.	Low - VOC Turf-Tite Medium "Hot" Blue	083675-240131	24	27
240136S	32 oz.	Low - VOC Turf-Tite Medium "Hot" Blue	083675-240124	12	26
240124C	Gallon	Low - VOC Turf-Tite Medium "Hot" Blue	083675-240117	6	52



WELL-TITE™ PVC MEDIUM "HOT" BLUE CEMENT

- Medium-bodied blue colored cement for PVC pipe and fittings Up to 8" diameter.
- Very fast setting cement formulated for wet conditions and/or quick pressurization and fast installation.
- Recommended for ALL grades and types of PVC pipe and fittings potable water, pressure pipe and DWV.
- Fades to clear in sunlight.
- No primer needed on non-pressure DWV up to 4" diameter, where local codes permit.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

3046S	16 oz.	Well-Tite PVC Medium "Hot" Blue	083675-304635	24	27
3036S	32 oz.	Well-Tite PVC Medium "Hot" Blue	083675-303621	12	26
3024	Gallon	Well-Tite PVC Medium "Hot" Blue	083675-302419	6	52

Product No.	Size	Description	UPC Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	----------	-----------------	----------

POLAR-WELD™ PVC ALL WEATHER CEMENT

- Medium-bodied clear cement for use on PVC pipe and fittings.
- Formulated for fast initial set-up at temperatures down to -5°F to 110°F. Sch. 40 and Sch. 80.
- Meets ASTM D-2564.
- Recommended for all grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- No primer needed on non-pressure DWV up to 4" in diameter, where local codes permit.

2666S	4 oz.	Polar-Weld PVC All Weather	083675-026667	24	9
2656S	8 oz.	Polar-Weld PVC All Weather	083675-026568	24	16
2646S	16 oz.	Polar-Weld PVC All Weather	083675-026469	24	27
2636S	32 oz.	Polar-Weld PVC All Weather	083675-026360	12	26
2624	Gallon	Polar-Weld PVC All Weather	083675-026247	6	52



SUPER 30® #213 WHITE EXTRA HEAVY BODY

- Very heavy bodied medium-setting white cement for use on PVC pipe and fittings up to 30" diameter.
- Formulated for quick installation.
- Recommended for all grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Builds up for large diameter installation to fill gaps.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

21336S	32 oz.	#213 White	083675-213326	12	26
--------	--------	------------	---------------	----	----



SUPER 30® #1800 GRAY EXTRA HEAVY BODY

- Very heavy bodied medium-setting gray cement for use on PVC pipe and fittings up to 30" diameter.
- Formulated for quick installation.
- Recommended for all grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Builds up for large diameter installation to fill gaps.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

1846S	16 oz.	# 1800 Gray	083675-018464	24	27
1836S	32 oz.	# 1800 Gray	083675-018365	12	26
1824	Gallon	# 1800 Gray - Wide Mouth Can	083675-018242	6	52



PVC HEAVY DUTY CLEAR CEMENT

- Heavy-bodied clear cement for PVC pipe and fittings up to 12" diameter for Sch. 40 and Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe, conduit and DWV.
- Recommended application temperature 40°F to 110°F.
- Thick formula fills gaps in large diameter pipe and loose fitting joints.
- Meets ASTM D-2564.

1566S	4 oz.	PVC Heavy Duty Clear	083675-015661	24	9
1556S	8 oz.	PVC Heavy Duty Clear	083675-015562	24	14
1546S	16 oz.	PVC Heavy Duty Clear	083675-015463	24	27
1536S	32 oz.	PVC Heavy Duty Clear	083675-015364	12	26
1524	Gallon	PVC Heavy Duty Clear	083675-015241	6	52



PVC MEDIUM CLEAR CEMENT

- Medium-bodied clear cement for PVC pipe and fittings up to 6" diameter for Sch. 40 and Sch. 80.
- Recommended application temperature 40°F to 110°F.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Meets ASTM D-2564.

1266S	4 oz.	PVC Medium Clear	083675-012660	24	9
1256S	8 oz.	PVC Medium Clear	083675-012561	24	16
1246S	16 oz.	PVC Medium Clear	083675-012462	24	27
1236S	32 oz.	PVC Medium Clear	083675-012363	12	26
1224	Gallon	PVC Medium Clear	083675-012240	6	52



PVC REGULAR CLEAR CEMENT

- Regular-bodied clear cement for PVC pipe and fittings up to 4" diameter for Sch. 40 and up to 2" for Sch. 80.
- Recommended application temperature 40°F to 110°F.
- Sets up quickly.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Meets ASTM D-2564.

2266S	4 oz.	PVC Regular Clear	083675-022669	24	9
2256S	8 oz.	PVC Regular Clear	083675-022560	24	16
2246S	16 oz.	PVC Regular Clear	083675-022461	24	27
2236S	32 oz.	PVC Regular Clear	083675-022362	12	26
2224	Gallon	PVC Regular Clear	083675-022249	6	52



Product No.	Size	Description	UPC Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	----------	-----------------	----------



PVC REGULAR CLEAR FAST SET CEMENT

- Regular-bodied clear cement for PVC pipe and fittings up to 4" diameter for Sch. 40 and up to 2" for Sch. 80.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Sets up quickly.

2866S	4 oz.	PVC Regular Clear Fast Set Cement	083675-028661	24	9
2856S	8 oz.	PVC Regular Clear Fast Set Cement	083675-028562	24	16
2846S	16 oz.	PVC Regular Clear Fast Set Cement	083675-028463	24	27
2836S	32 oz.	PVC Regular Clear Fast Set Cement	083675-028364	12	26
2824	Gallon	PVC Regular Clear Fast Set Cement	083675-028241	6	52

PVC HEAVY DUTY GRAY CEMENT

- Heavy-bodied gray cement for PVC pipe and fittings up to 12" diameter for Sch. 40 and up to 2" for Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Recommended application temperature 40°F to 110°F.
- Thick formula fills gaps in large diameter pipe and loose fitting joints.
- Meets ASTM D-2564.

1756S	8 oz.	PVC Heavy Duty Gray	083675-017566	24	16
1746S	16 oz.	PVC Heavy Duty Gray	083675-017467	24	27
1736S	32 oz.	PVC Heavy Duty Gray	083675-017368	12	26
1724	Gallon	PVC Heavy Duty Gray - Wide Mouth Can	083675-017245	6	52



PVC MEDIUM GRAY CEMENT

- Medium-bodied gray cement for PVC pipe and fittings up to 6" diameter for Sch. 40 and Sch. 80.
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2564.

1666S	4 oz.	PVC Medium Gray	083675-016668	24	9
1656S	8 oz.	PVC Medium Gray	083675-016569	24	16
1646S	16 oz.	PVC Medium Gray	083675-016460	24	27
1636S	32 oz.	PVC Medium Gray	083675-016361	12	26
1624	Gallon	PVC Medium Gray	083675-016248	6	52



MULTI PURPOSE CLEAR CEMENT

- Regular-bodied clear cement for PVC, ABS or CPVC pipe and fittings up to 4" diameter.
- Recommended for pipe and fittings Sch. 40 and Sch. 80, potable water, pressure pipe and DWV.
- Recommended application temperature 40°F to 110°F.
- Meets performance requirements of ASTM D-2564, D-2235, F-493.

6266S	4 oz.	Multi Purpose Regular Clear	083675-062665	24	9
6256S	8 oz.	Multi Purpose Regular Clear	083675-062566	24	16
6246S	16 oz.	Multi Purpose Regular Clear	083675-062467	24	27
6236S	32 oz.	Multi Purpose Regular Clear	083675-062368	12	26
6224	Gallon	Multi Purpose Regular Clear	083675-062245	6	52

ABS CEMENTS

ABS MEDIUM BLACK CEMENT

- Medium-bodied black cement for ABS pipe and fittings up to 6" diameter.
- Recommended application temperature 40°F to 110°F.
- Meets ASTM D-2235.
- For all non-pressure applications.
- For ALL types and grades of ABS pipe and fittings and DWV.



4466S	4 oz.	ABS Medium Black	083675-044661	24	9
4456S	8 oz.	ABS Medium Black	083675-044562	24	16
4446S	16 oz.	ABS Medium Black	083675-044463	24	27
4436S	32 oz.	ABS Medium Black	083675-044364	12	26
4424	Gallon	ABS Medium Black	083675-044241	6	52



Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
ABS SPECIAL MILKY CLEAR CEMENT					
<ul style="list-style-type: none"> Medium-bodied milky clear cement for ABS pipe and fittings up to 6" diameter. Recommended application temperature 40°F to 110°F. Meets ASTM D-2235. 			<ul style="list-style-type: none"> Fast curing for or all non-pressure applications. For All types and grades of ABS pipe and fittings and DWV. 		
4136S	32 oz.	ABS Special Milky Clear	083675-041363	12	26



CPVC CEMENTS

CPVC MEDIUM ORANGE CEMENT

<ul style="list-style-type: none"> Medium-bodied orange colored cement for use on CPVC pipe and fittings up to 6" diameter. For C.T.S. (Copper Tube Size) and Sch. 80, potable water pressure pipe. 			<ul style="list-style-type: none"> Recommended application temperature 40°F to 110°F. Meets ASTM F-493. 		
3266S	4 oz.	CPVC Medium Orange	083675-032668	24	9
3256S	8 oz.	CPVC Medium Orange	083675-032569	24	16
3246S	16 oz.	CPVC Medium Orange	083675-032460	24	27
3236S	32 oz.	CPVC Medium Orange	083675-032361	12	26



PRIMERS & CLEANERS

BLUE PRIMER - NSF LISTED

<ul style="list-style-type: none"> Blue-tinted aggressive primer for use on PVC and CPVC pipe and fittings. Blue color fades to clear in direct sunlight. 			<ul style="list-style-type: none"> Formulated to work with all "TITE" products. Meets ASTM F-656. 		
8056S	8 oz.	Prime-Tite Blue Primer - NSF Listed	083675-080560	24	16
8046S	16 oz.	Prime-Tite Blue Primer - NSF Listed	083675-080461	24	27
8036S	32 oz.	Prime-Tite Blue Primer - NSF Listed	083675-080362	12	26
8024	Gallon	Prime-Tite Blue Primer - NSF Listed	083675-080249	6	45



LOW-V.O.C. PURPLE PRIMER - NSF LISTED

<ul style="list-style-type: none"> Purple-tinted aggressive primer for use on PVC and CPVC pipe and fittings. Exceeds new environmental requirements and meets various California district rules. 			<ul style="list-style-type: none"> For use in areas where plumbing code calls for verification that a primer has been used. Removes surface dirt, grease and grime as well as softens the pipe surface to allow a fast, secure solvent weld. 		
8766S	4 oz.	LOW-VOC Purple Primer - NSF Listed	083675-087668	24	9
8756S	8 oz.	LOW-VOC Purple Primer - NSF Listed	083675-087569	24	16
8746S	16 oz.	LOW-VOC Purple Primer - NSF Listed	083675-087460	24	27
8736S	32 oz.	LOW-VOC Purple Primer - NSF Listed	083675-087361	12	26
8724	Gallon	LOW-VOC Purple Primer - NSF Listed	083675-087248	6	45
5824	Gallon	LOW-VOC Purple Primer - NSF Listed Wide Mouth Can	083675-058248	6	45



LOW-VOC CLEAR PRIMER - NSF LISTED

<ul style="list-style-type: none"> A clear aggressive primer for use on PVC and CPVC pipe and fittings. All schedules and all diameters. Meets ASTM F-656. 			<ul style="list-style-type: none"> Removes surface dirt, grease and grime as well as softens the pipe surface to allow a fast, secure solvent weld. 		
9366S	4 oz.	LOW-VOC Clear Primer - NSF Listed	083675-093669	24	9
9356S	8 oz.	LOW-VOC Clear Primer - NSF Listed	083675-093560	24	16
9346S	16 oz.	LOW-VOC Clear Primer - NSF Listed	083675-093461	24	27
9336S	32 oz.	LOW-VOC Clear Primer - NSF Listed	083675-093362	12	26
9324	Gallon	LOW-VOC Clear Primer - NSF Listed	083675-093249	6	45



LOW-VOC PURPLE PRIMER/CLEANER

<ul style="list-style-type: none"> Purple-tinted all purpose primer/cleaner for use on PVC and CPVC pipe and fittings. Removes surface dirt, grease and grime as well as softens the pipe surface to allow a fast, secure solvent weld. 			<ul style="list-style-type: none"> Less aggressive than clear primer and purple primer. Exceeds new environmental requirements and meets various California district rules. 		
8866S	4 oz.	LOW-VOC Purple Primer/Cleaner	083675-088665	24	9
8856S	8 oz.	LOW-VOC Purple Primer/Cleaner	083675-088566	24	16
8846S	16 oz.	LOW-VOC Purple Primer/Cleaner	083675-088467	24	27
8836S	32 oz.	LOW-VOC Purple Primer/Cleaner	083675-088368	12	26
8824	Gallon	LOW-VOC Purple Primer/Cleaner	083675-088245	6	45



Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------



LOW - VOC CLEAR CLEANER

- Clear cleaner for ABS, PVC and CPVC pipe and fittings.
- Fast acting cleaner removes surface dirt, grease and grime.
- All schedules and all diameters.
- Flows freely and evaporates quickly.
- Exceeds new environmental requirements and meets various California district rules.

7366S	4 oz.	LOW-VOC Clear Cleaner	083675-073661	24	9
7356S	8 oz.	LOW-VOC Clear Cleaner	083675-073562	24	16
7346S	16 oz.	LOW-VOC Clear Cleaner	083675-073463	24	27
7336S	32 oz.	LOW-VOC Clear Cleaner	083675-073364	12	26
7324	Gallon	LOW-VOC Clear Cleaner	083675-073241	6	45

ACCESSORIES

SOLVENT CEMENT AND PRIMER ACCESSORIES

- Standard replacement daubers specifically sized for 4 oz., 8 oz., 16 oz. and 32 oz. cement/primer cans.
- Standard replacement cans.
- Brush and roller applicator tops for 16 & 32 oz. cans.



31299	4 oz.	Dauber	038753-312996	48	2
31309	8 oz.	Dauber	038753-313092	48	2
31310	16 oz.	Dauber	038753-313108	48	2
31312	32 oz.	Dauber	038753-313122	48	2
31313	16/32 oz.	Dauber for CPVC	038753-313139	48	2
31257	16/32 oz.	Brush top Dauber	038753-312576	48	4
31275	12"	Gallon can roller applicator	038753-312750	12	5
31276	12"	Gallon can swab applicator	038753-312767	12	5
MTC66	4 oz.	Cement Can	038753-313047	24	3
31305	8 oz.	Cement Can	038753-313054	24	3
31306	16 oz.	Cement Can	038753-313061	24	3
31307	32 oz.	Cement Can	038753-313078	12	3
30901	1 Gallon	Wide Mouth Can	038753-309019	6	3



ADJUSTABLE DAUBER

- For applying solvent cement and primers.
- Fits can sizes 1/2 pint through quart.
- Specially constructed easy open, easy close sealing controls evaporation of solvents and prevents spillage.
- Dauber is unbreakable.
- Designed to adjust to various can dimensions and allows application of the proper amount of cement to ensure a good solvent weld.

31300		Adjustable plastic dauber w/ 1/2" ball	038753-313009	100	3
31301		Adjustable plastic dauber w/ 1" ball	038753-313016	100	3
31302		Adjustable plastic dauber	038753-313023	50	2



CEMENT CARRIER

- Designed to make it easier to keep cement and cleaner ready for use on the job.
- Caddy holds two 32 oz. cans.
- Patented.

31250	32 oz. can	Cement Carrier	038753-312507	12	3
-------	------------	----------------	---------------	----	---